


























































## 1 - 001 SINGLE CORE SILICONE CABLES FLEXIBLE AND SOLID

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C001 im:18	FG4/2 (SIF-SIAF-GS)	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
CA01 im:4	EI2-FG4/2 (EI2 SIF - SIAF)	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
CB01 im:4	AL-FG4/2 (K/FG4/2 - K/SIF)	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
C002 im:14	UG4/2 (SID-SIA-SIR)	CE		180°C	300/500V	COPPER SOLID	Class 1
CA02 im:4	UG4/2 - THT (SID 250°C)	CE		250°C	300/500V	COPPER SOLID	Class 1
CB02 im:2	AL-UG4/2 (K/UG4/2 - K/SID)	CE		180°C	300/500V	COPPER SOLID	Class 1
C007 im:13	THT (SIF 250°C-SIAF 250°C)	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
C044 im:8	FG4/2 - HT (SIF 220°C-SIAF 220°C)	CE		220°C	300/500V	COPPER FLEXIBLE	Class 5
C045 im:7	FG4/300-E (SIF 300V-SIAF 300V-GS 300V)	CE		180°C	300V	COPPER FLEXIBLE	Class 5
C048 im:4	RG4/2-THT	CE		250°C	300/500V	COPPER SEMISOLID	Class 2
C051 im:1	H03S - K	CE	IMO SHARP	180°C	300/300V	COPPER FLEXIBLE	Class 5
C052 im:17	H05S - K	CE	IMO SHARP	180°C	300/500V	COPPER FLEXIBLE	Class 5
C053 im:18	H05S - U	CE	IMO SHARP	180°C	300/500V	COPPER SOLID	Class 1
C071 im:10	N2GFAF	CE	DE	180°C	300/300V	COPPER FLEXIBLE	Class 5
C074 im:21	SIL/0100 F-Tin or Bare Copper (N)2GFAF	CE	< VDE-REG >	180°C	300/300V	COPPER FLEXIBLE	Class 5
C072 im:10	N2GFA	CE	DE	180°C	300/300V	COPPER SOLID	Class 1
C075 im:8	SIL/0100 U (N)2GFA	CE	< VDE-REG >	180°C	300/300V	COPPER SOLID	Class 1
C087 im:7	SIL/0400 F	CE	< VDE-REG >	180°C	0.6/1 kV	COPPER FLEXIBLE	Class 5
C086 im:8	SIL/0500 F		< VDE-REG >	180°C	1.8/3 kV	COPPER FLEXIBLE	Class 5
C156 im:9	UL Style3123-CSA I A/B FT-2	CE	UL, CSA	150°C	600V	COPPER FLEXIBLE	UL Standard
C157 im:15	UL Style3132-CSA I A/B FT-2 SIL	CE	UL, CSA	150°C	300V	COPPER FLEXIBLE	UL Standard
C159 im:10	UL Style3133-CSA I A/B FT-2	CE	UL, CSA	150°C	600V	COPPER FLEXIBLE	UL Standard
C160 im:10	UL Style3134-CSA I A/B FT-2	CE	UL, CSA	150°C	600V	COPPER FLEXIBLE	UL Standard
C161 im:12	UL Style3135 Flex-CSA I A/B FT-2	CE	UL, CSA	200°C	600V	COPPER FLEXIBLE	UL Standard
C172 im:1	UL Style3135 Solid-CSA I A/B FT-2	CE	UL, CSA	200°C	600V	COPPER SOLID	UL Standard
C173 im:0	UL Style3135 Solid	CE	UL	200°C	600V	COPPER SOLID	UL Standard
C162 im:9	UL Style3136-CSA I A/B FT-2	CE	UL, CSA	150°C	300V	COPPER FLEXIBLE	UL Standard
C163 im:10	UL Style3367-CSA I A/B FT-2	CE	UL, CSA	200°C	300V	COPPER FLEXIBLE	UL Standard
C166 im:8	UL Style3099-CSA I A/B FT-2	CE	UL, CSA	150°C	300V	COPPER FLEXIBLE	UL Standard
C170 im:2	UL Style3572 Flex	CE	UL	200°C	1000V	COPPER FLEXIBLE	UL Standard
C171 im:1	UL Style3572 Solid	CE	UL	200°C	1000V	COPPER SOLID	UL Standard
C401 im:0	UL Style3136	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C402 im:0	UL Style3099	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C403 im:0	UL Style3099 VW-1	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C404 im:0	UL Style3132 SIL	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C405 im:0	UL Style3132 SIL VW1	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C410 im:0	UL Style3123	CE	UL	150°C	600V	COPPER FLEXIBLE	UL Standard
C411 im:0	UL Style3123 VW-1	CE	UL	150°C	600V	COPPER FLEXIBLE	UL Standard
C412 im:0	UL Style3133	CE	UL	150°C	600V	COPPER FLEXIBLE	UL Standard







C413	im:0	UL Style3133 VW-1	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C414	im:0	UL Style3134	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C415	im:0	UL Style3134 VW-1	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C421	im:0	UL Style3367	CE		200°C	300V	COPPER FLEXIBLE	UL Standard
C422	im:0	UL Style3367 VW-1	CE		200°C	300V	COPPER FLEXIBLE	UL Standard
C425	im:0	UL Style3135 Flex	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C426	im:0	UL Style3135 Flex VW-1	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C427	im:0	UL Style3135 Solid	CE		200°C	600V	COPPER SOLID	UL Standard
C428	im:0	UL Style3135 Solid VW-1	CE		200°C	600V	COPPER SOLID	UL Standard
C434	im:0	UL Style 3572 Flex	CE		200°C	1000V	COPPER FLEXIBLE	UL Standard
C435	im:0	UL Style 3572 Solid	CE		200°C	1000V	COPPER SOLID	UL Standard

**2 - 002 SINGLE CORE SILICONE/FIBERGLASS CABLES FLEXIBLE AND SOLID**



Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C003 im:17	FG4T2/2 Glass or Polyester (SIF/GL-SIAF/GL-GSV)	CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
CA03 im:7	FG4T2/2-Ni Glass or Polyester	CE		200°C	300/500V	NIKEL	
C004 im:12	UG4T2/2 Glass or Polyester (SID/GL-SIA/GL-SIR/GL)	CE		200°C	300/500V	COPPER SOLID	Class 1
C006 im:17	FG4T2/12	CE		200°C	600V	COPPER FLEXIBLE	Class 5
C008 im:14	THT/VT (SIF/GL 250°C-SIAF/GL 250°C)	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
C009 im:12	FG4T2/12-THT	CE		250°C	600V	COPPER FLEXIBLE	Class 5
C030 im:10	THT/VT-Ni	CE		250°C	300/500V	NIKEL	
C043 im:8	FG4T2/2-HT (SIF/GL 220°C-SIAF/GL 220°C)	CE		220°C	300/500V	COPPER FLEXIBLE	Class 5
C046 im:8	FG4T2/300-E Glass or Polyester (300V SIF/GL-SIAF/GL)	CE		200°C	300V	COPPER FLEXIBLE	Class 5
C047 im:6	FG4T2/2-R Glass or Polyester	CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
CA51 im:15	H05SJ - K	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
CA59 im:7	H05SJ - U	CE		180°C	300/500V	COPPER SOLID	Class 1
C059 im:14	UG4T2	CE		180°C	300/500V	COPPER SOLID	Class 1
C060 im:14	UG4T2-T200°C	CE		200°C	300/300V	COPPER SOLID	Class 1
C062 im:13	RG4T2-T200°C	CE		200°C	300/300V	COPPER FLEXIBLE	UL Standard
C084 im:9	SIL/0100 F-T2- Tin or Bare Copper	CE	< VDE-REG >	180°C	300/300V	COPPER FLEXIBLE	Class 5
C085 im:10	SIL/0100 U-T2	CE	< VDE-REG >	180°C	300/300V	COPPER SOLID	Class 1
C150 im:0	UL Style3132 VW-1 - CSA I A/B FT-2 SIL/VT	CE	 	150°C	300V	COPPER FLEXIBLE	UL Standard
C151 im:12	UL Style3068-CSA I A/B FT-2	CE	 	150°C	300V	COPPER FLEXIBLE	UL Standard
C152 im:11	UL Style3069-CSA I A/B FT-2	CE	 	150°C	600V	COPPER FLEXIBLE	UL Standard
C153 im:11	UL Style3070-CSA I A/B FT-2	CE	 	150°C	600V	COPPER FLEXIBLE	UL Standard
C154 im:11	UL Style3071-CSA I A/B FT-2	CE	 	200°C	600V	COPPER FLEXIBLE	UL Standard
C155 im:12	UL Style3122-CSA I A/B FT-2	CE	 	200°C	300V	COPPER FLEXIBLE	UL Standard
C158 im:15	UL Style3132-CSA I A/B FT-2 SIL/VT	CE	 	150°C	300V	COPPER FLEXIBLE	UL Standard
C164 im:7	UL Style3067 ALLOY CONDUCTOR	CE		200°C	600V	ALLOY	
C165 im:7	UL Style3076 ALLOY CONDUCTOR	CE		150°C	300V	ALLOY	
C167 im:8	UL Style3144-CSA I A/B FT-2	CE	 	200°C	600V	COPPER FLEXIBLE	UL Standard
C168 im:8	UL Style3172-CSA I A/B FT-2	CE	 	200°C	600V	COPPER FLEXIBLE	UL Standard

C169	im:12	UL Style3301-CSA I A/B FT-2	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C406	im:0	UL Style3132 SIL/VT	CE		150°C	300V	COPPER FLEXIBLE	UL Standard
C407	im:0	UL Style3132 SIL/VT VW-1	CE		150°C	300V	COPPER FLEXIBLE	UL Standard
C408	im:0	UL Style3068	CE		150°C	300V	COPPER FLEXIBLE	UL Standard
C409	im:0	UL Style3068 VW-1	CE		150°C	300V	COPPER FLEXIBLE	UL Standard
C416	im:0	UL Style3069	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C417	im:0	UL Style3069 VW-1	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C418	im:0	UL Style3070	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C419	im:0	UL Style3070 VW-1	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C420	im:0	UL Style3301	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
C423	im:0	UL Style3122	CE		200°C	300V	COPPER FLEXIBLE	UL Standard
C424	im:0	UL Style3122 VW-1	CE		200°C	300V	COPPER FLEXIBLE	UL Standard
C429	im:0	UL Style3071	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C430	im:0	UL Style3071 VW-1	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C431	im:0	UL Style3172	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C432	im:0	UL Style3172 VW-1	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C433	im:0	UL Style3144	CE		200°C	600V	COPPER FLEXIBLE	UL Standard
C436	im:0	UL Style3067 ALLOY CONDUCTOR	CE		200°C	600V	ALLOY	
C437	im:0	UL Style3067 ALLOY CONDUCTOR VW-1	CE		200°C	600V	ALLOY	
C438	im:0	UL Style3076 ALLOY CONDUCTOR	CE		150°C	300V	ALLOY	
C439	im:0	UL Style3076 ALLOY CONDUCTOR VW-1	CE		150°C	300V	ALLOY	

**3 - 007 SINGLE CORE SIL.OR SIL./GLASS CABLES DOUBLE INSULATION**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
CA52	im:9 H05S - K (D.I.)	CE		180°C	300/500V	COPPER FLEXIBLE Class 5
CA53	im:1 H05S-U (D.I.)	CE		180°C	300/500V	COPPER SOLID Class 1
C055	im:14 FG4G4 450/750 V	CE		180°C	450/750V	COPPER FLEXIBLE Class 5
C057	im:16 UG4G4 450/750 V	CE		180°C	450/750V	COPPER SOLID Class 1
C056	im:15 FG4G4T2 450/750 V	CE		180°C	450/750V	COPPER FLEXIBLE Class 5
C058	im:17 UG4G4T2 450/750 V	CE		180°C	450/750V	COPPER SOLID Class 1
C077	im:13 SiLHSiL F	CE	< VDE-REG >	180°C	300/300V	COPPER FLEXIBLE Class 5
C078	im:14 SiLHSiL F-T2	CE	< VDE-REG >	180°C	300/500V	COPPER FLEXIBLE Class 5
C079	im:13 SiLHSiL U	CE	< VDE-REG >	180°C	300/300V	COPPER SOLID Class 1
C080	im:15 SiLHSiL U-T2	CE	< VDE-REG >	180°C	300/500V	COPPER SOLID Class 1

**4 - 005 NEON CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C041	im:12 NEON CABLES SILICONE EN50143 Several Variants			180°C	5000/10000V	COPPER FLEXIBLE Class 5
C042	im:7 NEON CABLES PVC EN50143 Several Variants			70°C	5000/10000V	COPPER FLEXIBLE Class 5

**5 - 003 SINGLE CORE GLASS/GLASS CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C015	im:4 VHT/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE Class 5



<b>C016</b>	im:14	VH/GR.2/RR	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C017</b>	im:18	VH/GR.2/Ni	CE		300°C	300/300V	NIKEL	
<b>C018</b>	im:12	VH//GR.2/R.Ni	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C020</b>	im:11	VH-IT/2G/Ni	CE		300°C	300/500V	NIKEL	
<b>CA20</b>	im:2	VH-IT/2G/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C032</b>	im:9	VHIT/GR.2/Ni	CE		300°C	300/500V	NIKEL	
<b>C033</b>	im:10	VHIT/GR.2/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C036</b>	im:9	VHIT/GR.2 Several Variants	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5

**6 - 004 SINGLE CORE PTFE/GLASS CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type		
<b>C010</b>	im:15	VTC/RR	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C011</b>	im:16	VTC/Ni	CE		300°C	300/300V	NIKEL	
<b>C012</b>	im:14	VTC/R.Ni	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C013</b>	im:8	V2TC/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C014</b>	im:7	V2TC/RR V2TC/RST	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA14</b>	im:2	VTR/Ni	CE		300°C	300/300V	NIKEL	
<b>C021</b>	im:8	VTC/Ni - 1T	CE		300°C	300/300V	NIKEL	
<b>C022</b>	im:2	VTC/R.Ni-1T	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C031</b>	im:11	TSVVR Several Variants	CE		300°C	300/500V	NIKEL	
<b>C037</b>	im:6	TSVR-Ni	CE		250°C	300/300V	NIKEL	
<b>C038</b>	im:4	TSVVR Several Variants	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5

**7 - 010 SINGLE CORE CABLES-SPECIAL CONSTR.**









Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type		
<b>C034</b>	im:6	TS Several Variants	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C035</b>	im:5	TS/Ni	CE		250°C	300/500V	NIKEL	
<b>C300</b>	im:3	VH - RR - FRENI			250°C	48V	COPPER FLEXIBLE	Class 5
<b>C301</b>	im:6	FT2G4T2			200°C	48V	COPPER FLEXIBLE	Class 5

**8 - 006 VARIOUS CABLES WITH PVC INSULATION**





Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type		
<b>C261</b>	im:10	FRDR - FR 300/500 - FR3 HT	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C262</b>	im:5	FROR CC	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5

**9 - 011 MULTICORE SILICONE/SILICONE CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type		
<b>C023</b>	im:18	FG4OG4/2 Several Variants with or without armour	(SIHF) CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA23</b>	im:3	FG4OG4/2 S - Several Variants with shielding	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CB23</b>	im:1	FG4OG4/2 G-T200 FG4OG4/2 X-T200 FG4OG4/2 CC-T200	CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C024</b>	im:13	FG4OG4T2/2 Several Variants	(SIHF/GL) CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C028</b>	im:11	FG4W 180 or 250°C	(SIFZ-w) CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
<b>CA28</b>	im:2	UG4W	(SIDZ-w) CE		180°C	300/500V	COPPER SOLID	Class 1

<b>C029</b>	im:7	FG4WT2-THT/Ni	CE		250°C	300/300V	NIKEL	
<b>C303</b>	im:10	SIHF G	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C063</b>	im:15	H05SS-F Several Variants	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA63</b>	im:9	H05SSD3-K H05SSD3T-K Several Variants	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CB63</b>	im:6	H05SS-F G (VM)	CE		180°C	300/500V	COPPER EXTRA-FLEX.	Class 6
<b>CA64</b>	im:6	UG4OG4 Several Variants	CE		180°C	300/500V	COPPER SOLID	Class 1
<b>C088</b>	im:4	SIL/0100 FZ-W	(SIFZ-w VDE) CE	<VDE-REG >	180°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C175</b>	im:0	cUL MULTICONDUCTOR CABLE 150-300	CE		150°C	300V	COPPER FLEXIBLE	UL Standard
<b>C176</b>	im:0	cUL MULTICONDUCTOR CABLE 200-300	CE		200°C	300V	COPPER FLEXIBLE	UL Standard
<b>C451</b>	im:1	UL Style 4389 150-600	CE		150°C	600V	COPPER FLEXIBLE	UL Standard
<b>C452</b>	im:1	UL Style 4389 200-600	CE		200°C	600V	COPPER FLEXIBLE	UL Standard

**10 - 012 MULTICORE SILICONE/PVC CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C302</b>	im:7 EI2-SiF-PV/P(fl)			90°C	48V	COPPER FLEXIBLE	Class 5
<b>C305</b>	im:5 EI2-SiF-PV/P(E)	CE		90°C	48V	COPPER FLEXIBLE	Class 5
<b>C304</b>	im:7 SIHF-PV G	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C054</b>	im:20 FG4OR Several Variants	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA54</b>	im:5 FG4ORY Several Variants	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C061</b>	im:14 FG4DR	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C064</b>	im:10 UG4OR Several Variants	CE		90°C	300/500V	COPPER SOLID	Class 1
<b>C076</b>	im:19 SiLHYW (fl)	CE	<VDE-REG >	90°C	300/300V	COPPER FLEXIBLE	Class 5
<b>C081</b>	im:18 SiLHYW(rd) Several Variants	CE	<VDE-REG >	90°C	300/300V	COPPER FLEXIBLE	Class 5
<b>CA81</b>	im:8 SiLHYW(rd) G (VM)	CE	<VDE-REG >	90°C	300/300V	COPPER EXTRA-FLEX.	Class 6
<b>C082</b>	im:16 SiMHYW Several Variants	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5

**11 - 015 MULTICORE CABLES-SPECIAL CONSTR.**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C019</b>	im:15 VHO-A Several Variants	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
<b>CA19</b>	im:1 VHTO-A R.Ni	CE		270°C	300/500V	---	
<b>C025</b>	im:10 FG4OT2/2 G	CE		200°C	300/300V	COPPER FLEXIBLE	Class 5

**12 - 022 MULTICORE CABLE WITH HELICOIDAL ASSEMBLY**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C308</b>	im:0 PVC D.I./RY - PVC D.I./PE	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C309</b>	im:1 PVC/RY - PVC/PE	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C310</b>	im:3 FG4TX/2-RY FG4TX/2-PE	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C311</b>	im:2 FG4T2X/2-RY	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C312</b>	im:0 FG4TX D.I. - PE	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5

**13 - 016 SPECIAL PRODUCTS**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C026</b>	im:14 SVFR			500°C		IRON-ALLUMINIUM-INOX etc.	



**C027** im:9 CORDONETTI 200°C SUPPORT

**14 - 017 THERMOREGULATION CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C221 im:6	FRDR-T			70°C	48V	ALLOY
C222 im:7	FRDR-TA			70°C	48V	ALLOY
C223 im:6	FROPSR-T			70°C	48V	ALLOY
C224 im:6	FROASR-T			70°C	48V	ALLOY
C225 im:4	FROR-TA			70°C	48V	ALLOY
C226 im:5	FROR-T			70°C	48V	ALLOY
C231 im:21	VHDT2 Several Variants			250°C	48V	ALLOY
C232 im:16	VHOT2-T Several Variants			250°C	48V	ALLOY
C233 im:14	VHOT2-TR Several Variants		(PT 100)	250°C	48V	COPPER FLEXIBLE Class 5
C241 im:8	FG50-TS UG50-TS			250°C	48V	ALLOY
C251 im:11	FG4OG4-T			180°C	48V	ALLOY
C252 im:5	FG4OG4-TA			180°C	48V	ALLOY
C253 im:8	FG4OASG4-T			180°C	48V	ALLOY
C254 im:8	FG4OG4-TS			180°C	48V	ALLOY

**15 - 018 PROTECTION AND INSULATION SLEEVES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C101 im:9	G.801			250°C	---	
C102 im:11	G.810/N - G.830/SIL - G.840/SIL/CAR			180°C	---	
C103 im:9	G.600			180°C	---	
C105 im:7	G810/S			250°C	---	
C106 im:3	G.810/R			250°C	---	
C107 im:1	G.600R			150°C	---	
C104 im:13	TS1801 (kV 1,50 - 2,50 - 4,00)			200°C	---	

**16 - 031 MONOTUBES FOR STEAM IRON SYSTEMS**


Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C801 im:8	MONOTUBO con cavo VDE SIL/PVC	CE		90°C	300/300V	COPPER FLEXIBLE Class 5
C805 im:9	MONOTUBO con cavo HAR SILICONE	CE		180°C	300/500V	COPPER FLEXIBLE Class 5
C806 im:3	MONOTUBO con cavo SPECIALE SILICONE	CE		180°C	300/300V	COPPER EXTRA-FLEX. Class 6
C815 im:8	MONOTUBO con cavo HAR H05RR-F o H05BB-F	CE		90°C	300/500V	---

**17 - 030 STEAM TUBES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C851 im:9	Tubo EPDM RIVESTITO	CE		130°C	---	
C852 im:5	Tubo EPDM	CE		130°C	---	
C853 im:1	Tubo SILICONE NON RIVESTITO	CE		250°C	---	

**32 - S14 VARIOUS CABLES WITH PVC INSULATION**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
-------	--------------	----	----------	------------------------	-----------------	----------------



*Clemi*



# LIST OF CATALOGUE PRODUCTS

**T001**

**HIGH TEMPERATURE** [www.blf.it](http://www.blf.it) - [blf@blf.it](mailto:blf@blf.it)

C307 im:0 B03VV-F-T/RY - B03VV-F-T/PE



70°C 300/300V COPPER FLEXIBLE Class 5